



Flexi Everyday - Flexi Foot Variations

Angled Feet to work with more challenging roof falls. Mini Foot for lightweight services. Walkwat Matt for roof protection

Flexi Foot Variations

To complement our range of Flexi Feet we have a number of variations on the standard Flexi Foot With Strut.

The foot only options are available in 200, 300 and 500mm with angle pitch variants of 2.5 & 5.0 degrees.



PH-FO-350-5.0-S



PH-FO-200

Code	Description	Length mm	Width mm	Height mm	Safe Working Load**	Weight
PH-FO-200	Flexi Foot – 200mm for vertical strut / M10 thread	200	200	85	100kg	2.3kg
PH-FO-350	Flexi Foot – 350mm for vertical strut	350	350	110	150kg	5.7kg
PH-FO-350-2	Flexi Foot – 350mm for vertical 82x41mm strut	350	350	110	150kg	5.7kg
PH-FO-350-2.5-S	Flexi Foot – 350mm for vertical 2.5 degree	350	350	125	150kg	5.9kg
PH-FO-350-5.0-S	Flexi Foot – 350mm for vertical 5.0 degree	350	350	140	150kg	6.1kg
PH-FO-500	Flexi Foot – 500mm for vertical strut	500	500	110	150kg	10.5kg
PH-FO-500-2	Flexi Foot – 500mm for vertical 82x41mm strut	500	500	110	150kg	10.5kg
PH-FO-500-2.5	Flexi Foot – 500mm for vertical 2.5 degree	500	500	130	150kg	10.7kg
PH-FO-500-5.0	Flexi Foot – 500mm for vertical 5.0 degree	500	500	150	150kg	10.9kg

Flexi Mini Foot

Lightweight support that may be used with horizontal or vertical strut to support low level cable tray and other services.

F-MF-160



Code	Description	Length mm	Width mm	Height mm	Safe Working Load**	Weight
F-MF-160	Flexi Mini Foot – 160mm	160	160	60	50kg	230g

Walkway Mat

Walkway mats may be combined to define a safe access path whilst protecting the roof surface.

WW-MAT-500



Code	Description	Length mm	Width mm	Height mm	Safe Working Load**	Weight
WW-MAT-500	Walkway Mat – 500mm	500	500	45	150kg	14kg



Pump House
 Glaisdale Drive East
 Nottingham
 NG8 4LY
 Tel: +44(0)115 900 5858
www.flexisupportsystems.co.uk
sales@flexisupportsystems.co.uk



everyday



heavy



access



solar

