




EVERYDAY




■ FLEXI FOOT VARIATIONS

TO COMPLEMENT OUR TRADITIONAL RANGE OF FLEXI FEET WE HAVE A NUMBER OF VARIATIONS


■ FLEXI FOOT VARIATIONS

Code	Description	Foot Application	Material	Length (mm)	Width (mm)	Height (mm)	Safe Working Load*	Weight
F-MF-160	Flexi Mini Foot	41 x 41mm strut vertically or horizontally	PVC	160	160	60	50kg	230gms
PH-FO-200	200mm square Flexi Foot	41 x 41mm strut vertically	Crumb Rubber	200	200	85	100kg	2.3kg
PH-FO-200-R	200mm square Flexi Foot, round core	48mm RHS Legs vertically	Crumb Rubber	200	200	85	100kg	2.3kg
F-FO-320	320mm square Flexi Foot	48mm RHS Legs & 41 x 41mm strut vertically	90% Polyprop/10% GRP	320	320	81	250kg	1.6kg
PH-FO-350	350mm square foot	41 x 41mm strut vertically	Crumb Rubber	350	350	110	350kg	5.7kg
PH-FO-350-2.5	350mm square, 2.5 degree cut, round core	48mm RHS Legs vertically	Crumb Rubber	350	350	125	150kg	5.9kg
PH-FO-350-5.0	350mm square, 5.0 degree cut, round core	48mm RHS Legs vertically	Crumb Rubber	350	350	140	350kg	6.1kg
PH-FO-350-2	350mm square, 82 x 41mm core	82 x 41mm (back to back) strut vertically	Crumb Rubber	350	350	110	350kg	5.7kg
PH-FO-350-2.5-S	350mm square, 2.5 degree cut, 41 x 41mm core	41 x 41mm strut vertically	Crumb Rubber	350	350	125	350kg	5.9kg
PH-FO-350-5.0-S	350mm square, 5.0 degree cut, 41 x 41mm core	41 x 41mm strut vertically	Crumb Rubber	350	350	140	350kg	6.1kg
PH-FO-500	500mm square foot	41 x 41mm strut vertically	Crumb Rubber	500	500	110	500kg	10.5kg
F-FO-500	500mm square foot	48mm RHS Legs & 41 x 41mm strut vertically	90% Polyprop/10% GRP	500	500	110	500kg	5.6kg
PH-FO-500-2.5	500mm square, 2.5 degree cut, round core	48mm RHS Legs vertically	Crumb Rubber	500	500	130	500kg	10.7kg
PH-FO-500-5.0	500mm square, 5.0 degree cut, round core	48mm RHS Legs vertically	Crumb Rubber	500	500	150	500kg	10.9kg
PH-FO-500-5.0-2	500mm square, 5.0 degree cut, 82 x 41mm core	82 x 41mm (back to back) strut vertically	Crumb Rubber	500	500	150	500kg	10.9kg
PH-FO-500-2	500mm square, 82x41mm core	82 x 41mm (back to back) strut vertically	Crumb Rubber	500	500	110	500kg	10.5kg
PH-FO-500-5.0-S	500mm square, 5.0 degree cut, 41 x 41mm core	41 x 41mm strut vertically	Crumb Rubber	500	500	150	500kg	10.9kg
PH-FO-500-R	500mm square	48mm RHS Legs Vertically	Crumb Rubber	500	500	110	500kg	10.9kg


LIGHT




HEAVY



SOLAR



ACCESS




FLEXI-EVERYDAY Flexi Foot Variations

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@flexisupportsystems.co.uk or visit www.flexisupportsystems.co.uk





EVERYDAY



FLEXI FOOT VARIATIONS

TO COMPLEMENT OUR TRADITIONAL RANGE OF FLEXI FEET WE HAVE A NUMBER OF VARIATIONS

FLEXI MINI FOOT




Lightweight support that may be used with horizontal or vertical strut to support low level cable tray and other services


Code	Description	Length mm	Width mm	Height mm	Safe working load*	Weight
F-MF-160	Flexi Mini Foot - 160mm	160	160	60	50kg	230g

FLEXI FOOT VARIATIONS

Angled feet that suit more challenging roof falls.




Code	Description	Length mm	Width mm	Height mm	Safe working load*	Weight
PH-FO-350-5.0-S	350mm square, 5.0 degree cut, 41x41mm core	350	350	140	350kg	6.1kg



Code	Description	Length mm	Width mm	Height mm	Safe working load*	Weight
PH-FO-200	200mm square Flexi Foot	200	200	85	100kg	2.3kg


WALK WAY MAT




Walk Way mats may be combined to define a safe access path whilst protecting the roof surface.

Code	Description	Length mm	Width mm	Height mm	Safe working load*	Weight
PH-WW-MAT-500	Walk Way Mat - 500mm	500	500	45	150kg	14kg
PH-WW-MAT-1000-17	Walk Way Mat - 1000mm	1000	1000	45	600kg	17kg


LIGHT




HEAVY



SOLAR



ACCESS



FLEXI-EVERYDAY
Flexi Foot Variations

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@flexisupportsystems.co.uk or visit www.flexisupportsystems.co.uk

DIVERSITECH[®]
INTERNATIONAL